

Tannin™ Has It.

LIONPROOF 338

tannincorp.com

COMPOSITION

A robust, durable water and oil repellent, based on C6 chemistry.

SPECIFICATIONS

Appearance	Milky White Emulsion
Ionic nature	Nonionic/anionic
pH	2.5-6.0
Solids	18.5-19.5%

KEY PROPERTIES

LIONPROOF 338 is highly effective on all fibers, but particularly synthetics and leather. **LIONPROOF 338** is comparable to C8 repellents on most substrates.

APPLICATIONS

Leather: 6-8% wet-end application (apply to fresh bath at end of cycle)

25% Spray solution, 4-6 gms/sq. ft.

For leather, dry at 150°F. As with all fluoropolymers, test additional finishing components for compatibility and affect on performance before scaling up to large scale.

Excellent for water/alcohol and oil requirements. Contains C6 – no PFOA.



Tannin Corporation
65 Walnut Street
Peabody, MA 01960, USA
Phone: +1.978.532.4010
Fax: +1.978.532.5536
sales@tannincorp.com

Tannin Mexico S.A. de C.V.
Blvd. San Crispin 130
Fracc. Ind. San Crispin
Leon, Gto. 37527, Mexico
teléfono: +52.477.770.9499
tanninmex@terra.com.mx

The Supplier makes no warranty of any kind, expressed or implied, concerning this product or its use. The user assumes all risk of use or handling, regardless of whether the same is in accordance with the direction or suggestion of the supplier.