

Tannin™ Has It.

LIONPROOF SW

tannincorp.com

COMPOSITION

A silicone / polymer emulsion blended with a wax compound for use in making waterproof pull up leathers. For best results it should be fixed with a metal salt after application.

SPECIFICATIONS

Appearance	White liquid / paste
Activity	60 – 70%
Charge	Anionic
Density (Lb/Gal)	7.5 – 8.5
pH (10% Solution)	8.0 – 9.0
Storage Stability	One year at room temperature. Optimum storage temperature is between 15°C and 30°C
Freeze/Thaw Stability	Sensitive to freezing Do not store below 5°C
Lightfastness	Good
Electrolyte Stability	Fair
Emulsification	Mix before use. Readily soluble in warm water. Mix 1:1 with warm water until homogeneous. Emulsify to 1:4 at 30°C to 60°C.

KEY PROPERTIES

LIONPROOF SW is a single product waterproof system with excellent hydrophobic properties to give softness and water proofing with enhanced Maeser flexes > 60,000 flexes.

- Waterproofing fatliquor for chrome tanned leathers.
- High Maeser flexes achieved.
- Promotes Low water absorption.
- For use in making Waterproof Pull-up Leathers

APPLICATIONS

Recommended usage is 8% to 16% on Blue shaved weight.



Tannin Corporation
65 Walnut Street
Peabody, MA 01960, USA
Phone: +1.978.532.4010
Fax: +1.978.532.5536
sales@tannincorp.com

Tannin Mexico S.A. de C.V.
Blvd. San Crispin 130
Fracc. Ind. San Crispin
Leon, Gto. 37527, Mexico
teléfono: +52.477.770.9499
tanninmex@terra.com.mx