

# Tannin™ Has It.

## LIONWAX 15

[tannincorp.com](http://tannincorp.com)

### COMPOSITION

A hard petroleum-based wax compound.

### SPECIFICATIONS

|                       |  |
|-----------------------|--|
| Appearance            | Off-white wax  |
| Activity              | 100%   |
| Melting Point         | 50 - 56°C  |
| Charge                | No charge  |
| Density (Lb/Gal)      | 6.8 (± 0.2)  |
| Storage Stability     | Indefinite at optimum storage.<br>Optimum storage temperature is<br>between 15°C and 30°C. |
| Freeze/Thaw Stability | Not sensitive to freezing.   |
| Emulsification        | Not soluble in water.  |

### KEY PROPERTIES

**LIONWAX 15** is a hard wax that can be used alone or with other products to produce stuffed, semi-stuffed, or pull-up leathers on a heated roll coater.

- Good filling and firming of leathers where it is used
- Does not form fatty spew on leather surface
- Clean, bright, and level colors
- Extreme pull-up affects

### APPLICATIONS

8 – 16 gm / sq ft @ 60 - 80°C on a heated Roll Coater.



Tannin Corporation  
65 Walnut Street  
Peabody, MA 01960, USA  
Phone: +1.978.532.4010  
Fax: +1.978.532.5536  
[sales@tannincorp.com](mailto:sales@tannincorp.com)

Tannin Mexico S.A. de C.V.  
Blvd. San Crispin 130  
Fracc. Ind. San Crispin  
Leon, Gto. 37527, Mexico  
teléfono: +52.477.770.9499  
[tanninmex@terra.com.mx](mailto:tanninmex@terra.com.mx)