

Tannin™ Has It.

LIONWAX RX-60

tannincorp.com

COMPOSITION

A wax compound based on a blend of petroleum waxes and greases that can be applied to waterproof crust.

SPECIFICATIONS

Appearance	Yellow/brown wax
Activity	100%
Melting Point	40 - 50°C
Charge	No charge
Density (Lb/Gal)	6.8 (± 0.2)
Solubility	Insoluble in water.
Storage Stability	Indefinite at optimum storage temperature between 15°C and 30°C.
Freeze/Thaw Stability	Not sensitive to freezing.
Lightfastness	Good
Emulsification	Insoluble in water.

KEY PROPERTIES

LIONWAX RX-60 is a wax compound that can be applied to waterproof or non waterproof crust leathers to make stuffed, semi-stuffed, or pull-up leathers on a heated roll coater.

- Maintains resistance to static water absorption
- Good filling and firming properties
- Clean, bright, and level colors
- Excellent pull-up effects

APPLICATIONS

8 – 16 gm / sq ft @ 50 - 60°C on a heated Roll Coater.



Tannin Corporation
65 Walnut Street
Peabody, MA 01960, USA
Phone: +1.978.532.4010
Fax: +1.978.532.5536
sales@tannincorp.com

Tannin Mexico S.A. de C.V.
Blvd. San Crispin 130
Fracc. Ind. San Crispin
Leon, Gto. 37527, Mexico
teléfono: +52.477.770.9499
tanninmex@terra.com.mx

The Supplier makes no warranty of any kind, expressed or implied, concerning this product or its use. The user assumes all risk of use or handling, regardless of whether the same is in accordance with the direction or suggestion of the supplier.