

Tannin™ Has It.

LIONWAX RX-63-T

tannincorp.com

COMPOSITION

A wax compound based on a blend of petroleum waxes, greases, and silicone that can be applied to make pull up crust.

SPECIFICATIONS

Appearance	Yellow wax
Activity	100%
Melting Point	50-60°C
Charge	No Charge
Density (Lb/Gal)	6.8 (± 0.2)
Solubility	Insoluble in water
Storage Stability	Indefinite at optimum storage temperature between 15°C and 30°C.
Freeze/Thaw	Stability not sensitive to freezing.
Lightfastness	Good
Emulsification	Insoluble in water. Emulsify 1:4 at 50°C to 60°C.

KEY PROPERTIES

LIONWAX RX-63-T is a wax compound which can be applied to waterproof crust leathers to make stuffed, semi-stuffed, or pull-up leathers on a heated roll coater.

- Maintains resistance to static water absorption
- Increases Maeser results on waterproof leathers
- Good filling and firming properties
- Excellent Pull-up effects

APPLICATIONS

Recommended usage is 8 – 16 gm / sq ft.



Tannin Corporation
65 Walnut Street
Peabody, MA 01960, USA
Phone: +1.978.532.4010
Fax: +1.978.532.5536
sales@tannincorp.com

Tannin Mexico S.A. de C.V.
Blvd. San Crispin 130
Fracc. Ind. San Crispin
Leon, Gto. 37527, Mexico
teléfono: +52.477.770.9499
tanninmex@terra.com.mx